



CE EMC IP20 RoHS

Type	Part N°	Dimensions (mm)	Colour	Lumen (lm)	Input V	Beam °	Power Max (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
TUNE CCT 6W	<b>BDPL0806CCTB</b>	Ø 115x32h	3000 - 4200 - 6000K	480	175÷240	120°	6	Ø 105	119x119x47h	0,12
TUNE CCT 12W	<b>BDPL0812CCTB</b>	Ø 170x32h	3000 - 4200 - 6000K	960	175÷240	120°	12	Ø 155	174x174x47h	0,21

- Incasso a LED tondo ad alta potenza 230V CCT**
- Selettore per scelta colore (3000K - 4200K - 6000K)
  - Installazione semplice e veloce
  - Funziona direttamente a tensione di rete con alimentatore incorporato
  - Lunga durata

- Round extra powerful 230V recessed CCT LED downlight**
- Switch for color setting (3000K - 4200K - 6000K)
  - Easy and quick installation
  - Works directly with mains voltage (Built-in driver)
  - Long life time

- CCT LED Rundenbastrahler 230V**
- Switch für Farbauswahl (3000K - 4200K - 6000K)
  - Einfache und schnelle Installation
  - Betrieb direkt auf 230V mit ein gebautem Led-Treiber
  - Lange Lebensdauer

- Encastrement LED rond CCT haute puissance 230V**
- Programmeur de teintes (3000K - 4200K - 6000K)
  - Installation simple et rapid
  - Alimentation intégrée, branchement direct sur le réseau
  - Longue durée de vie

- Focos empotrables a LED de alta potencia 230V CCT**
- Selector de colores (3000K - 4200K - 6000K)
  - Instalación rápida y fácil
  - Alimentación directa 230V (convertidor integrado)
  - Larga duración

Connettere direttamente a 175÷240V  
Connect direct to 175÷240V

**CONNECT  
230V  
DIRECT**

Driver incorporato  
Built-in driver



- 3000K
- 4200K
- 6000K

